



HP Pavilion x360 m3-u103dx HP Pavilion x360 m3-u103dx Keyboard Replacement

How to replace the keyboard for the HP Pavilion x360 m3-u103dx.

Written By: Teresita Aragon



INTRODUCTION

In this guide you will be required to remove the keyboard and disconnect three wires from the device in order to replace the keyboard. You will need to use a iFixit Pro Tech Toolkit.

This task requires patience and attention to detail.



TOOLS:

- [Metal Spudger](#) (1)
 - [Phillips #00 Screwdriver](#) (1)
 - [Heavy-Duty Spudger](#) (1)
-


Step 1 — Keyboard



- Power off Device.

⚠ Working device while it is powered on may cause damage to laptop or electric shock.

Step 2



- Flip over laptop
- Remove the rubber foot with a Metal Spudger

Step 3




- Remove the screws from the bottom of the laptop using a Phillips 00 Screwdriver.
- 5 Phillips 2.4 x 5.7 mm screws.
- 5 Phillips 2.0 x 5.0 mm screws.
- ⓘ Make sure to keep different screw types separated.

Step 4



- Flip the laptop over to screen and keyboard side.
 - Using a Metal Spudger pop open keyboard from base of laptop.
- ⚠ Be cautious of three wires on the inside of the keyboard connecting it to the motherboard.

Step 5



- Disconnect the three connected cable ribbons connected to the motherboard by gently pulling them out of their connectors.

Step 6



- After ribbon cables have been disconnected, carefully lift up keyboard to disconnect from base of laptop.

To reassemble your device, follow these instructions in reverse order.