




LG G3 Motherboard Cover Assembly Replacement

This guide shows how to remove or replace the motherboard cover assembly in the LG G3 (D855).

Written By: Dominik Schnabelrauch



INTRODUCTION

Use this guide to remove or replace the motherboard cover assembly in the LG G3 (D855).



TOOLS:

- [Spudger](#) (1)
- [Phillips #00 Screwdriver](#) (1)
- [iFixit Opening Picks set of 6](#) (1)



PARTS:

- [LG G3 Rear Panel \(T-Mobile\)](#) (1)
- [LG G3 Rear Panel \(ATT\)](#) (1)
- [LG G3 Battery](#) (1)
- [LG G3 Speaker Assembly \(ATT\)](#) (1)
- [LG G3 Speaker Assembly \(T-Mobile\)](#) (1)
- [LG G3 Speaker Assembly \(Sprint\)](#) (1)
- [LG G3 Motherboard Cover \(Sprint\)](#) (1)
- [LG G3 Motherboard Cover \(T-Mobile\)](#) (1)
- [LG G3 Motherboard Cover \(AT&T\)](#) (1)

Step 1 — Back Cover



 Power off your phone before beginning disassembly.

- Insert a thumbnail, or a prying tool like a spudger, into the notch at the bottom left of the back cover.
- Pry the back cover up to separate its plastic clips.

Step 2



- Lift the back cover to release the rest of the plastic clips and remove it.
- ❗ In case you can't lift the back cover completely, slide your fingernail or your prying tool around the midframe to release the remaining clips.
- 🔧 To reinstall the back cover, press it firmly into place until you hear a snap from the plastic clips to form a seamless connection with the rear side of the phone.

Step 3 — Battery



- Use a fingernail or a prying tool at the marked notch to lever the battery out of its recess.

Step 4



- Lift the battery out of its recess and remove it.

Step 5 — Loudspeaker




- Remove the four Phillips #00 screws (4 mm length).

Step 6



- Insert a thumbnail, or a prying tool like a spudger, into the notch at the bottom left of the back cover you used earlier to remove the back cover.
- Pry up the plastic panel, including the loudspeaker, until you can get a good grip.

Step 7



- Carefully remove the plastic panel including the loudspeaker by gently pulling it away from the phone assembly.

Step 8 — Motherboard Cover Assembly




- Remove the eight Phillips #00 screws (4 mm length).

Step 9



- Insert an opening pick between the bottom right corner of the motherboard cover and the motherboard.
- Pry up the motherboard cover to open the plastic clips which hold the cover in its place.
 - ❗ The clips can be a bit resistive. If you're having trouble prying up the motherboard cover, slightly rotate the opening pick sideways to make the process easier.
- Work your way along the right edge.

Step 10



- Carefully lift the right edge of the motherboard cover.
 - ❗ The remaining plastic clips should open during this process or can be unhinged easily by hand.
- Remove the motherboard assembly.

If possible, turn on your device and test your repair before installing new adhesive and resealing.

Take your e-waste to an [R2 or e-Stewards certified recycler](#).

Repair didn't go as planned? Try some [basic troubleshooting](#), or ask our [Answers Community](#) for help.