



# Nintendo Switch Pro Controller Battery Replacement

Welcome! Does the battery in your controller...

Written By: Daniel Tagalog



# INTRODUCTION

Welcome! Does the battery in your controller not last as long as it used to or not at all? You must be looking to replace the battery in your Nintendo Switch Pro Controller, well you have come to the right place! Below you will find instructions for replacing the battery in your controller, read them carefully and follow the steps in order from one to six.

The Switch Pro Controller uses JIS screws. Be sure not to use a Phillips screwdriver to remove them, as it will potentially strip the screws.

NOTE: an improperly sync Switch Pro controller will not charge properly. To determine if your battery is faulty and needs replacing, you can first re-sync your controller and, while plugged in, check within the Switch controllers menu if it is charging properly.

CAUTION: The handling of any swollen batteries should be done with the utmost care. For information on how to identify, what to do with, how to handle, and how to dispose of swollen batteries follow the link below.

[What to do with a swollen battery](#)



## TOOLS:

[JIS Driver Set](#) (1)



## PARTS:

[Nintendo CTR-003 Battery](#) (1)

---

## Step 1 — Remove the screws



- Flip the controller over so the model stickers face the ceiling.
- Use a [JIS](#) #00 screwdriver to remove the two black 8.4 mm screws that secure the handles, located at the ends of the handles.

## Step 2 — Remove the handle covers



- Carefully remove the handle covers by pulling them away from the main body.

### Step 3 — Remove the screws



- Use a JIS #00 screwdriver to remove the four silver 6.8 mm screws that secure the clear back plastic cover.

### Step 4 — Unclip the plastic cover



- Carefully pry away the clear plastic cover using your fingernail.

## Step 5 — Remove the clear plastic cover



- Remove the clear plastic cover.

## Step 6 — Remove the battery



- Remove the lithium-ion battery by using a fingernail or plastic opening tool to pry it up on the left side.

**i** Only a small amount of force is needed.

---

To reassemble your device, follow these instructions in reverse order.

For optimal performance, [calibrate your newly installed battery](#) after completing this guide.

Take your e-waste to an [R2 or e-Stewards certified recycler](#).

Repair didn't go as planned? Try some [basic troubleshooting](#), or ask our [Answers community](#) for help.