Mac Pro 2009-2012 RAM Replacement

Written By: BeanMan56

INTRODUCTION

Replace faulty sticks of RAM

⚙ ## PARTS:

- 8GB OWC Memory Upgrade Kit (1)
- 16GB OWC Memory Upgrade Kit (1)
- 32GB OWC Memory Upgrade Kit (8 core only) (1)

This document was generated on 2022-03-13 02:07:09 PM (MST).

Step 1 — Remove the side panel

- Lift the latch at the back of the computer

- Lift the side panel

This document was generated on 2022-03-13 02:07:09 PM (MST).

© iFixit — CC BY-NC-SA

www.iFixit.com

Page 3 of 5

Step 2 — Remove the Processor Board

- Press both latches to unlock the bracket and then pull it towards you

- Press where you see the circles

⚠️ You shouldn't need to apply much force.

Step 3 — Remove the old RAM

- Push the RAM tabs down to release the RAM

ⓘ When reinstalling the RAM it will take some force to install it properly!

ⓘ Repeat this step for each stick of RAM you want to replace.

This document was generated on 2022-03-13 02:07:09 PM (MST).

Step 4

- From these guides: [2009 Mac Pro CPU upgrade (single socket)](#) [Mac Pro 2009-2012 Case Replacement](#)

- Photo Credits: Josh Calvetti, Sam Goldheart, Maitland Thompson, Dan, Idrees, Stéphane MILOUX, Troy weglinski,

To reassemble your device, follow these instructions in reverse order.

This document was generated on 2022-03-13 02:07:09 PM (MST).