



Blu Studio 5.5 Back Panel Assembly Removal

Prerequisite Only

Written By: Luis Gomez-Atehortua





TOOLS:

- [iFixit Opening Tools](#) (1)
 - [Phillips #000 Screwdriver](#) (1)
-

Step 1 — Battery



- Locate the notch to remove the back panel at the lower left corner of the panel.
- Insert the plastic opening tool or a fingernail into the notch.
- Apply force upwards until back panel becomes loosened.

Step 2



- Remove the loosened back panel and set aside.
- Locate the notch to remove the battery.

Step 3



- Insert a plastic opening tool or your fingernail into the notch and apply force upwards until the battery is loosened.
- Remove the battery and set aside.

Step 4 — Back Panel Assembly



- Locate all twelve screws along the back panel:
 - Seven 5mm screws.
 - Five 3.5mm screws.
- Using a Phillips #000 screwdriver, remove all twelve screws.

Step 5



- Now that all the screws have been removed, use a plastic opening tool to carefully pry at each of the corners until loosened.
- ⚠ Be extra careful when prying open as it may damage or snap the thin sides of the panel.
- Place the plastic opening tool inside the loosened panel and gently push upwards and move along the phone to remove the back panel.
- Remove the panel as if you were turning the page of a book.

To reassemble your device, follow these instructions in reverse order.